



**2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - DUAL SCALE**

<b>15062</b>	Pro 50, 16mm spigot, 10 - 50 N·m, 7.5 - 37.5 lbf·ft
<b>15063</b>	Pro 100, 16mm spigot, 20 - 100 N·m, 15 - 75 lbf·ft
<b>15064</b>	Pro 200, 16mm spigot, 40 - 200 N·m, 30 - 150 lbf·ft
<b>15065</b>	Pro 300, 16mm spigot, 60 - 300 N·m, 50 - 220 lbf·ft

**2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - N·m ONLY**

<b>15072</b>	Pro 50, 16mm spigot, 10 - 50 N·m
<b>15073</b>	Pro 100, 16mm spigot, 20 - 100 N·m
<b>15074</b>	Pro 200, 16mm spigot, 40 - 200 N·m
<b>15075</b>	Pro 300, 16mm spigot, 60 - 300 N·m

**2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - lbf·ft ONLY**

<b>15082</b>	Pro 50, 16mm spigot, 7.5 - 37.5 lbf·ft
<b>15083</b>	Pro 100, 16mm spigot, 15 - 75 lbf·ft
<b>15084</b>	Pro 200, 16mm spigot, 30 - 150 lbf·ft
<b>15085</b>	Pro 300, 16mm spigot, 50 - 220 lbf·ft

**2 TORQUE HANDLES ADJUSTABLE 16mm SPIGOT - lbf·in ONLY**

<b>15092</b>	Pro 50, 16mm spigot, 90 - 440 lbf·in
<b>15093</b>	Pro 100, 16mm spigot, 200 - 800 lbf·in
<b>15094</b>	Pro 200, 16mm spigot, 400 - 1800 lbf·in
<b>15095</b>	Pro 300, 16mm spigot, 500 - 2500 lbf·in



**2 FEMALE TORQUE HANDLES ADJUSTABLE - DUAL SCALE**

<b>15102</b>	Pro 50, 9 x 12mm, 10 - 50 N·m, 7.5 - 37.5 lbf·ft
<b>15103</b>	Pro 100, 9 x 12 mm, 20 - 100 N·m, 15 - 75 lbf·ft
<b>15104</b>	Pro 200, 9 x 12 mm, 40 - 200 N·m, 30 - 150 lbf·ft
<b>15105</b>	Pro 200, 14 x 18 mm, 40 - 200 N·m, 30 - 150 lbf·ft
<b>15106</b>	Pro 300, 14 x 18 mm, 60 - 300 N·m, 50 - 220 lbf·ft
<b>15107</b>	Pro 340, 14 x 18 mm, 60 - 340 N·m, 50 - 250 lbf·ft
<b>15108</b>	Pro 400, 14 x 18 mm, 80 - 400 N·m, 60 - 300 lbf·ft

**2 FEMALE TORQUE HANDLES ADJUSTABLE - N·m ONLY**

<b>15112</b>	Pro 50, 9 x 12mm, 10 - 50 N·m
<b>15113</b>	Pro 100, 9 x 12 mm, 20 - 100 N·m
<b>15114</b>	Pro 200, 9 x 12 mm, 40 - 200 N·m
<b>15115</b>	Pro 200, 14 x 18 mm, 40 - 200 N·m
<b>15116</b>	Pro 300, 14 x 18 mm, 60 - 300 N·m
<b>15117</b>	Pro 340, 14 x 18 mm, 60 - 340 N·m
<b>15118</b>	Pro 400, 14 x 18 mm, 80 - 400 N·m

**2 FEMALE TORQUE HANDLES ADJUSTABLE - lbf·ft ONLY**

<b>15122</b>	Pro 50, 9 x 12mm, 7.5 - 37.5 lbf·ft
<b>15123</b>	Pro 100, 9 x 12 mm, 15 - 75 lbf·ft
<b>15124</b>	Pro 200, 9 x 12 mm, 30 - 150 lbf·ft
<b>15125</b>	Pro 200, 14 x 18 mm, 30 - 150 lbf·ft
<b>15126</b>	Pro 300, 14 x 18 mm, 50 - 220 lbf·ft
<b>15127</b>	Pro 340, 14 x 18 mm, 50 - 250 lbf·ft
<b>15128</b>	Pro 400, 14 x 18 mm, 60 - 300 lbf·ft

**2 FEMALE TORQUE HANDLES ADJUSTABLE - lbf·in ONLY**

<b>15132</b>	Pro 50, 9 x 12 mm, 90 - 440 lbf·in
<b>15133</b>	Pro 100, 9 x 12 mm, 200 - 800 lbf·in
<b>15134</b>	Pro 200, 9 x 12 mm, 400 - 1800 lbf·in
<b>15135</b>	Pro 200, 14 x 18 mm, 400 - 1800 lbf·in
<b>15136</b>	Pro 300, 14 x 18 mm, 500 - 2500 lbf·in
<b>15137</b>	Pro 340, 14 x 18 mm, 500 - 3000 lbf·in
<b>15138</b>	Pro 400, 14 x 18 mm, 700 - 3500 lbf·in

