

## SPECIFICATIONS

Metric				
Range	Order No.	Depth bar	Fine adjustment	Remarks
0 - 100mm	<b>500-150-20</b>	ø1.9mm rod	with thumb roller	—
0 - 100mm	<b>500-180-20*</b>	ø1.9mm rod	—	—
0 - 150mm	<b>500-151-20</b>	Blade	with thumb roller	—
0 - 150mm	<b>500-154-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside measurement
0 - 150mm	<b>500-155-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside and inside measurement
0 - 150mm	<b>500-158-20</b>	ø1.9mm rod	with thumb roller	—
0 - 150mm	<b>500-181-20*</b>	Blade	—	—
0 - 200mm	<b>500-152-20</b>	Blade	with thumb roller	—
0 - 200mm	<b>500-156-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside measurement
0 - 200mm	<b>500-157-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside and inside measurement
0 - 200mm	<b>500-182-20*</b>	Blade	—	—
0 - 300mm	<b>500-153</b>	Blade	with thumb roller	—
0 - 450mm	<b>500-500-10</b>	—	—	—
0 - 600mm	<b>500-501-10</b>	—	—	—
0 - 1000mm	<b>500-502-10</b>	—	—	—

\*without SPC data output

Inch/Metric				
Range	Order No.	Depth bar	Fine adjustment	Remarks
0 - 4"	<b>500-170-20</b>	ø3/40" rod	with thumb roller	—
0 - 4"	<b>500-195-20*</b>	ø3/40" rod	with thumb roller	—
0 - 6"	<b>500-171-20</b>	Blade	with thumb roller	—
0 - 6"	<b>500-174-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside measurement
0 - 6"	<b>500-175-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside and inside measurement
0 - 6"	<b>500-178-20</b>	ø3/40" rod	with thumb roller	—
0 - 6"	<b>500-196-20*</b>	Blade	with thumb roller	—
0 - 6"	<b>500-159-20*</b>	Blade	with thumb roller	Carbide-tipped jaws for outside measurement
0 - 6"	<b>500-160-20*</b>	Blade	with thumb roller	Carbide-tipped jaws for outside and inside measurement
0 - 8"	<b>500-172-20</b>	Blade	with thumb roller	—
0 - 8"	<b>500-176-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside measurement
0 - 8"	<b>500-177-20</b>	Blade	with thumb roller	Carbide-tipped jaws for outside and inside measurement
0 - 8"	<b>500-197-20*</b>	Blade	with thumb roller	—
0 - 8"	<b>500-163-20*</b>	Blade	with thumb roller	Carbide-tipped jaws for outside measurement
0 - 8"	<b>500-164-20*</b>	Blade	with thumb roller	Carbide-tipped jaws for outside and inside measurement
0 - 12"	<b>500-173</b>	Blade	with thumb roller	—
0 - 12"	<b>500-167</b>	Blade	with thumb roller	Carbide-tipped jaws for outside measurement
0 - 12"	<b>500-168</b>	Blade	with thumb roller	Carbide-tipped jaws for outside and inside measurement
0 - 12"	<b>500-193*</b>	Blade	with thumb roller	—
0 - 12"	<b>500-165*</b>	Blade	—	Carbide-tipped jaws for outside measurement
0 - 12"	<b>500-166*</b>	Blade	—	Carbide-tipped jaws for outside and inside measurement
0 - 18"	<b>500-505-10</b>	—	—	—
0 - 24"	<b>500-506-10</b>	—	—	—
0 - 40"	<b>500-507-10</b>	—	—	—

\*without SPC data output



500-502-10

500-501-10

500-500-10