

GROUP 331 DIGITAL INDICATORS

OXFORD PRECISION External Digital Micrometer

External Digital Micrometer 0-25mm/0-1"

Oxford external digital micrometer with large digital display, quick response speed and zero set at any point. Metric/inch measurement. Can be connected to a PC serial port via the SPC cable (supplied separately). **IP65** rating.

- Easy handling
- mm/Inch measurements
- Ball end cap for measuring curved surfaces
- Large digital display
- Quick response speed
- Zero set at any point
- **IP65** rating

Coolant Proof

IP65



Range	Order Code
0 - 25mm/0 - 1"	OXD-331 -6110K

Digital Electronic External Micrometer

Easy handling with a large digital display, quick response speed and zero set at any point. Metric/inch measurement. The micrometer can be connected to a PC serial port by the SPC cable provided. **IP54** rating.

Range: 0 - 25mm/0 - 1".

Resolution: 0.001mm/0.00005".

Measuring force: 5 - 10N.

Accuracy: -0.004mm.

IP54

Protected against dust ingress and fluid splash



With SPC Data Output

Range	Resolution	Order Code
0 - 25mm/0 - 1"	0.001mm/0.0005"	OXD-331 -5010K



OXFORD PRECISION IDM Digital Indicator

Features: Easy to use with clear digital LCD display. Large, easy-read 7.5mm LCD display. Soft-key touch for operator comfort, superior construction quality. **Response speed:** ≤0.5m/s. Auto power off.

Type IDM
Inch/metric conversion, zero reset, data hold, min. max display, fast display, auto power off.



inch mm CONVERTIBLE
TRAVEL 12.7mm / 0.5"
ZERO RESET
READING 0.001mm / .00005"
IP54
Protected against dust ingress and fluid splash

Description	Order Code
IDM Digital Indicator	OXD-331 -6020K

IDS Digital Indicator

Features: Easy to use with clear digital LCD display. Large, easy-read 7.5mm LCD display. Soft-key touch for operator comfort. Superior construction quality.

Response speed: ≤0.5m/s. Auto power off.



inch mm CONVERTIBLE
TRAVEL 12.7mm / 0.5"
ZERO RESET
READING 0.01mm / .0005"
IP54
Protected against dust ingress and fluid splash

Description	Order Code
IDS Digital Indicator	OXD-331 -6010K

KENNEDY Digital Protractor

PDV360
This digital protractor has a range of 360° split into 4 x 90° quadrants. It is simple to calibrate and the intelligent display changes orientation at 90° and 270° to remain readable. It has a 'V' groove on the top and bottom for easy placement on acute angled or cylindrical objects. 3V lithium battery gives up to 2000 hours use. Complete with a leatherette pouch that has a belt loop. **Resolution:** 0.1°



Range	Weight each	Order Code
360° (90° x 4)	10.2kg	KEN-331 -4020K

PRECISION EQUIPMENT