



**KOBE Speed Ratchets**

**SR375** 3/8" square drive, 10mm bolt capacity.  
**SR500** 1/2" square drive, 13mm bolt capacity.  
 Ball type retainer, disc type reversing action, compact, lightweight design, ideal for automotive work, front exhaust.

3/8 1/2

**Free speed:** 150rpm.  
**Air inlet thread:** 1/4" NPT.  
**Minimum air hose size (ID):** 10mm (3/8").  
**Air pressure:** 6.2bar/90psi.  
**Air consumption:** 4cfm\* (113ltr/m).  
**Torque:** 50ft./lbs.  
**Overall length:** 255mm.



**KBE - 270**

**Sound pressure level:** 89dBA 89dBA  
**Sound power level:** 96dBA 89dBA  
**Vibration level:** 4.0m/s<sup>2</sup> 4.0m/s<sup>2</sup>

\*Based on a 15 second cycle per minute average use.

Model Number	Square Drive	Weight each	Order Code
SR375	3/8"	1.10kg	<b>-2375K</b>
SR500	1/2"	1.10kg	<b>-2500K</b>

**Speed Ratchet 1/4" Square Drive**

**R7722**  
 Suitable for the removal and installation of threaded fasteners. Reversible hardened steel 1/4" square drive. Short body length allowing access into hard to reach areas. Planetary gears for longer life and smoother running. Low profile throttle for precise speed control. Rotating air inlet to prevent the air hose tangling.



1/4

**Drive size:** 1/4" (6mm).  
**Free speed:** 200rpm.  
**Recommended air pressure:** 6.2bar/90psi.  
**Air consumption:** 4cfm\* (113ltr/min).  
**Working torque range:** 7 ~ 27nm (5 ~ 20ft./lbs).  
**Air inlet thread:** 1/4" NPT.  
**Minimum air hose size (ID):** 10mm (3/8").  
**Sound pressure level:** 80dBA.  
**Sound power level:** 88dBA.  
**Vibration level:** 1.8m/s<sup>2</sup>.  
**Overall length:** 200mm.



**Protective rubber head cover**   **Lever operated throttle**   **Directional rear exhaust**   **Forward/Reverse lever switch**   **Adjustable air (speed) regulator**   **Vibration dampened rubber grip**

\*Based on a 15 second cycle per minute average use.

Overall Length	Weight each	Order Code
200mm	0.65kg	<b>-4010K</b>

**KOBE Speed Ratchets**

**FSR375** 3/8" square drive. **Working torque range:** 5 - 20ft.lbs (7 - 27Nm). **Overall length:** 205mm. **Free speed:** 200rpm.  
**FSR500** 1/2" square drive. **Working torque range:** 10 - 50ft.lbs (14 - 68Nm). **Overall length:** 265mm. **Free speed:** 150rpm.

3/8 1/2

Suitable for the removal and installation of threaded fasteners when doing automotive and light assembly work. Reversible hardened steel square drive. Rubber handle provides grip and operator comfort with reduced hand chill. Three planetary gears for longer life and smoother running. Rubber cover protects the ratchet head and the workpiece. Short body length allows access into hard to reach areas. Low profile teasing throttle for precise speed control. Rotating rear exhaust with baffle for reduced noise. Rotating air inlet to prevent the air hose tangling. Adjustable air regulator.

**Air inlet thread:** 1/4" NPT.  
**Minimum air hose size (ID):** 10mm (3/8").  
**Air pressure:** 6.2bar/90psi.  
**Air consumption:** 4cfm\* (113ltr/min).



**KBE - 270**

**Sound pressure level:** 84dBA 80dBA  
**Sound power level:** 88dBA 87dBA  
**Vibration level:** 1.8m/s<sup>2</sup> 2.6m/s<sup>2</sup>

\*Based on a 15 second cycle per minute average use.

Model Number	Square Drive	Working Torque Range	Overall Length	Weight each	Order Code
FSR375	3/8"	7 - 27Nm	205mm	640g	<b>-2360K</b>
FSR500	1/2"	14 - 68Nm	265mm	1.20kg	<b>-2300K</b>