



**KOBE Pistol Screwdriver Kit**

**SP1825K**

1/4" NPT air inlet thread for 10mm air hose, 90PSI air pressure, 4cfm\* air consumption, 45 - 115lbs/inch. 1/4" hex drive capacity.

**Sound pressure level:** 86dBA.

**Sound power level:** 102dBA.

**Vibration level:** 4.6m/s<sup>2</sup>.

**Overall length:** 178mm.

**Contents:**

- SP1825 screwdriver.
- Hexagon wrench and spanner.
- No.1, 2 and 3 x 50mm crosspoint bits.
- 4, 5 and 6mm x 50mm slotted bits.
- No.2 x 100mm crosspoint double-ended bit.

\*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code
1800	900g	<b>-3850K</b>



**Straight Screwdriver Kit**

**SS1525K**

1/4" NPT air inlet thread for 10mm air hose, 90PSI air pressure, 4cfm\* air consumption, 10 - 30lbs/inch torque. 1/4" hex drive capacity.

**Sound pressure level:** 90dBA.

**Sound power level:** 104dBA.

**Vibration level:** 3.2m/s<sup>2</sup>.

**Overall length:** 210mm.

**Contents:**

- SS1525 screwdriver.
- Two clutch springs:
- Clutch Spring No.06-703-13  
Dia 2.3mm; 1Nm - 3Nm
- Clutch Spring No.06-703-23  
Dia 1.8mm; 0.3Nm - 0.7Nm
- 2x spanners. Clutch adjusting wrench.
- 1/4 NPT nipple. Mini oil bottle.
- No.1 x 65mm crosspoint double ended bit.
- 5 x 50mm slotted bit.

\*Based on a 15 second cycle per minute average use.

Free Speed (rpm)	Weight each	Order Code
1700	900g	<b>-3800K</b>



**ABRASIVES & POWER TOOLS**

**KOBE Automatic Shut-off Screwdriver 0.6 - 5.1Nm**

**CSP005S**

Heavy-duty reverse action pistol grip screwdriver suitable for production and assembly applications.

Push to start type with auto shut-off clutch for precision applications. Three interchangeable torque springs allow for easy conversion for new applications. 1/4" hex drive. External torque adjustment does not require disassembly of the tool. Variable speed throttle. Ergonomically contoured grip for operator comfort. Handle exhaust directs air away from the workpiece and operator. Hanging ring included.

**Chuck size:** 1/4" (6mm) hex.

**Air inlet thread:** 1/4" NPT.

**Minimum air hose size (ID):** 3/8" (10mm).

**Green torque spring:**\* 0.6 - 2.1Nm (5 - 19in/lbs).

**Black torque spring:** 1.1 - 4.3Nm (10 - 38in/lbs).

**Yellow torque spring:** 1.7 - 5.1Nm (15 - 45in/lbs).

**Air pressure:** 6.3bar/90psi.

**Air consumption:** 4cfm\* (144ltr/min).

**Sound pressure level:** 84dBA.

**Sound power level:** 93dBA.

**Vibration level:** <0.5m/s<sup>2</sup>.



\*Based on a 15 second cycle per minute average use.



Overall Length	Weight each	Order Code
210mm	815g	<b>-3760K</b>

**PRODUCTS ARE ONLY AVAILABLE VIA YOUR DISTRIBUTOR**