

GROUP 220 FLAP WHEELS



Shaft mounted flap wheels can be used in portable air or electric power tools, including tyre buffers, flexible shafts and hand drills. Manufactured from highest quality industrial cloth. Used for a wide range of applications such as removal of rust, cleaning up welds and sanding wood prior to painting. Boxed in 10s except for 60 x 50 and 80 x 50 which are packed in 6's. Recessed hub design for maximum access in tight corners.

Applications

Final finishing of metal surfaces. Mis-match removal and deburring on machined components. Blending and finishing tool, tubes, dies, moulds, channels. Edge blending and cleaning. Surface preparation prior to painting and plating. Can be used on wood, plastic and fibreglass.



3mm Shank

Grit	Weight per 10	Order Code	YRK-220
30mm Dia x 10mm Height 20,400 MOS (rpm)			
P60	120g	-1010K	
P80	120g	-1020K	
P120	120g	-1030K	
P150	120g	-1040K	
P180	130g	-1050K	
P240	120g	-1080K	
P320	110g	-1100K	
30mm Dia x 15mm Height 20,400 MOS (rpm)			
P60	160g	-1510K	
P80	150g	-1520K	
P120	140g	-1530K	
P180	140g	-1550K	

6mm Shank

Grit	Weight per 10	Order Code	YRK-220
30mm Dia x 10mm Height 20,400 MOS (rpm)			
P40	163g	-1570K	
P60	163g	-1572K	
P80	155g	-1574K	
P120	155g	-1576K	
30mm Dia x 15mm Height 20,400 MOS (rpm)			
P40	200g	-1600K	
P60	210g	-1610K	
P80	200g	-1620K	
P120	200g	-1630K	
P150	210g	-1640K	
40mm Dia x 10mm Height 15,300 MOS (rpm)			
P80	244g	-1920K	
40mm Dia x 15mm Height 15,300 MOS (rpm)			
P40	330g	-2000K	
P60	340g	-2010K	
P80	330g	-2020K	
P120	330g	-2030K	
40mm Dia x 20mm Height 15,300 MOS (rpm)			
P40	400g	-2200K	
P60	400g	-2210K	
P80	390g	-2220K	
P120	400g	-2230K	
P180	380g	-2250K	
40mm Dia x 25mm Height 15,300 MOS (rpm)			
P40	490g	-2400K	
P60	480g	-2410K	
P80	460g	-2420K	
P120	450g	-2430K	
P180	550g	-2450K	

6mm Shank continued

Grit	Weight per 10	Order Code	YRK-220
40mm Dia x 30mm Height 15,300 MOS (rpm)			
P40	490g	-2600K	
P60	530g	-2610K	
P80	490g	-2620K	
50mm Dia x 10mm Height 12,300 MOS (rpm)			
P40	350g	-2800K	
P60	320g	-2810K	
P80	370g	-2820K	
P120	360g	-2830K	
50mm Dia x 15mm Height 12,300 MOS (rpm)			
P40	460g	-3000K	
P60	440g	-3010K	
P80	430g	-3020K	
P120	450g	-3030K	
50mm Dia x 20mm Height 12,300 MOS (rpm)			
P40	580g	-3500K	
P60	550g	-3510K	
P80	580g	-3520K	
P120	550g	-3530K	
50mm Dia x 25mm Height 12,300 MOS (rpm)			
P40	630g	-3800K	
P60	660g	-3810K	
P80	650g	-3820K	
P120	650g	-3830K	
P150	640g	-3850K	
50mm Dia x 30mm Height 12,300 MOS (rpm)			
P40	740g	-3900K	
P60	730g	-3910K	
P80	730g	-3920K	
P120	720g	-3930K	
P180	720g	-3940K	
50mm Dia x 40mm Height 12,300 MOS (rpm)			
P40	990g	-3950K	
P60	980g	-3960K	
P80	920g	-3970K	
P120	910g	-3980K	
P180	920g	-3990K	
60mm Dia x 20mm Height 10,200 MOS (rpm)			
P40	700g	-4000K	
P60	730g	-4010K	
P80	730g	-4020K	
P120	710g	-4030K	
60mm Dia x 30mm Height 10,200 MOS (rpm)			
P40	950g	-4500K	
P60	880g	-4510K	
P80	880g	-4520K	
P120	890g	-4530K	
P150	880g	-4540K	
P180	880g	-4550K	
P240	920g	-4580K	
60mm Dia x 40mm Height 10,200 MOS (rpm)			
P40	1100g	-5000K	
P60	1100g	-5010K	
P80	1070g	-5020K	
P120	1070g	-5030K	
P150	1020g	-5040K	
P180	1060g	-5050K	
P240	1050g	-5080K	
60mm Dia x 50mm Height 10,200 MOS (rpm)			
P40	1533g	-5100K	
P60	1383g	-5110K	
P80	1370g	-5120K	
P120	1420g	-5130K	
P180	1330g	-5140K	
80mm Dia x 20mm Height 7,700 MOS (rpm)			
P40	1100g	-5200K	
P60	1100g	-5210K	
P80	1100g	-5220K	
80mm Dia x 30mm Height 7,700 MOS (rpm)			
P40	1500g	-5500K	
P60	1400g	-5510K	
P80	1400g	-5520K	
P120	1400g	-5530K	
P320	1500g	-5600K	
80mm Dia x 40mm Height 7,700 MOS (rpm)			
P40	1900g	-6000K	
P60	1800g	-6010K	
P80	1800g	-6020K	
P120	1800g	-6030K	
80mm Dia x 50mm Height 7,700 MOS (rpm)			
P40	2500g	-6500K	
P60	2330g	-6510K	
P80	2330g	-6520K	
P120	2300g	-6530K	


Flap Wheel Sets

Shaft mounted flap wheels can be used in portable air or electric power tools, including tyre buffers, flexible shafts and hand drills. Manufactured from highest quality industrial cloth. Used for a wide range of applications such as removal of rust, cleaning up welds and sanding wood prior to painting. Recessed hub design for access in tight corners.

5 PIECES

5 Piece Set Contents:

30 x 15mm: P80,
40 x 15mm: P80,
50 x 15mm: P60,
50 x 20mm: P80,
60 x 30mm: P60.



Number of Pieces	Shank Size	Weight Per Set	Order Code
5	6mm	215g	-6950K


8 Piece Set Contents:

30 x 15mm: P60,
30 x 15mm: P120,
40 x 15mm: P60,

40 x 15mm: P120,
50 x 20mm: P80,
50 x 25mm: P60,
60 x 30mm: P40,
60 x 30mm: P80.

8 PIECES

6mm SHANK




Number of Pieces	Shank Size	Weight Per Set	Order Code
8	6mm	355g	-6980K

8 Piece 'Mini' Set Contents:

(*6mm Shank)
10 x 10mm: P60,
10 x 10mm: P120,
15 x 15mm: P80,
15 x 15mm: P120,
20 x 10mm: P60*,
20 x 10mm: P120*,
25 x 15mm: P80*,
25 x 25mm: P80*.

8 PIECES

3/6mm SHANKS



Number of Pieces	Shank Size	Weight Per Set	Order Code
8	3mm	200g	-7000K

SENATOR QUALITY TOOLING Flap Wheel Set

Contents:

30 x 15mm: P60,
30 x 15mm: P120,
40 x 15mm: P60,
40 x 15mm: P120,

50 x 25mm: P60,
50 x 25mm: P120,
60 x 30mm: P40,
60 x 30mm: P80.

8 PIECES

Number of Pieces	Shank Size	Weight Per Set	Order Code
8	6mm	370g	-6980K